



WaveGrip

Technical Spec: C-80 Applicator

| | |
|--|---|
| For Use With | Original Can Carrier Sleek Can Carrier Side Applied Can Carrier |
| Speed | 80 cans per minute |
| Dimensions: Metric | 1905mm (L) x 965.2mm (W) x 2006.6mm (H) |
| Dimensions: Imperial | 75" L 37.5" W 79" H. +- 4 |
| Conveyor Height | 36" + - 4" (leg extensions available) |
| Weight | 770kg / 1700 Lbs approximate |
| Output Format | 4, 6, 8 (short side leading) |
| Carrier Capacity: Standard 202/211 Can Carrier capacity: Sleek 202/ Can | 4545 4pk / 3030 6pk / 2272 8pk 5,262 4pk / 3508 6pk / 6,631 8pk |
| Con Size ml Can Size oz | 330ml, 440ml, 500ml, 568ml* 8oz, 12oz, 16oz, 19.2oz |
| Electrical | 110-220v single phase, 2A |
| Air | 50l/min @ 5 bar 1.6 cfm, 80 psi |
| PLC | Allen Bradley |
| Operator Interface | Push Button |
| In-feed Options | Left hand Single lane / 1 can Right hand Single lane / 1 can Inline Single lane / 1 can |
| Supplied as | Crated |
| Fault Identification | Light on Operator Station |
| Machine Access Panels | 4 Swinging Doors |
| Interlocks | Allen Bradley 44N-Z2NRS1C |
| Standards | CE, CUL, ASME |
| Warranty | 12 Months |

